



# STR

SYNTHETIC TURF RESOURCES

A sportgroup company



## TEELINE ELITE MAT

SKU: TLMAT

### MATERIALS

PRIMARY YARN POLYMER	Nylon
YARN CROSS SECTION	Diamond
STANDARD COLOR	Turf Green
UV STABILIZED	Yes
FABRIC CONSTRUCTION	Tufted
SECONDARY YARN POLYMER THATCH	N/A
SECONDARY YARN COLOR	N/A
PRIMARY BACKING	5/8" Armacell Pad
COATING TYPE	Urethane
POLYETHYLENE YARN DENIER / ENDS	7,000/8
TEXTURIZED THATCH DENIER / ENDS	N/A
SUSTAINABILITY	Recyclable
WARRANTY PERIOD	2 years

### FINISH FABRIC

### ENGLISH SYSTEM

### ASTM STANDARDS

NOMINAL SPECIFICATION	VALUE	UNITS	METHOD
TURF PILE HEIGHT	1	inch	D-5823
PAD HEIGHT	5/8	inch	D-5823
TOTAL HEIGHT	1 5/8	inch	D-5823
FACE WEIGHT	120	oz/yd <sup>2</sup>	D-5848
PAD WEIGHT	58	oz/yd <sup>2</sup>	D-5848
TOTAL FABRIC WEIGHT	178	oz/yd <sup>2</sup>	D-5848
PRIMARY BACKING WEIGHT	6	oz/yd <sup>2</sup>	D-5848
SECONDARY COATING WEIGHT	20	oz/yd <sup>2</sup>	D-5848
TUFT BIND	>8	lbs.	D-1335
GRAB TEAR STRENGTH (AVERAGE)	>200	lbs.	D-5034
LEAD CONTENT	<50	ppm	F-2765
TOTAL YARN LINEAR DENSITY	7,000	Denier	D-1577
ELONGATION TO BREAK	>60	%	D-2256
YARN BREAKING STRENGTH	>19	lbs.	D-2256
YARN MELTING POINT	428	°F	D-7138
MACHINE GAUGE	3/16	in	D-5793
FLAMMABILITY	Pass		D-2859
WATER PERMEABILITY	N/A	in/hr	DIN 18-035
FABRIC WIDTH	5x5	ft	None

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are ± 5%.